



The fact that these clamps are used on very small-bore hoses means that the material of the tube or hose can sometimes be very flexible, making it more difficult to ensure a leaktight assembly due to the possible deformation of the hose. In these cases, the inner-ring is key in helping to guarantee leaktightness as well as protecting the hose from being pinched during assembly.

MATERIAL: W1 Steel DC04 (EN 10139)
Stainless steel inner-ring
AISI 301

CORROSION RESISTANCE: 72 hours Salt Spray
(ASTM B-117)

Part Number	Ø Application mm	A ±0.2	B ±0.2	C ±0.2	D +0.3-0.2	F ±0.2	G ±0.2	E +0.1-0.02	Max. Pressure (Bar)	Box Quantity U.	Outer Box Quantity U.
03011009	7,5-8,5	9,3	5,5	6,0	13,0	8,8	7,8	0,8	27	1.000	8.000
03011010	8,0-9,5	10,3	6,0	6,0	14,0	9,8	7,8	0,8	27	1.000	8.000
03011029	9,0-10,5	11,3	6,5	6,5	15,0	10,8	7,8	0,8	27	1.000	8.000
03011037	10,0-11,5	12,3	7,0	6,5	16,0	11,8	7,8	0,8	27	500	8.000
03011045	10,5-12,5	13,3	7,5	6,5	17,0	12,8	7,8	0,9	27	500	8.000
03011053	11,5-13,3	14,3	8,0	7,0	18,5	13,8	8,8	1,0	22	500	2.000
03011061	13,0-15,3	16,3	8,5	7,0	20,5	15,8	8,8	1,1	22	500	4.000
03011070	15,0-17,3	18,5	9,5	7,0	23,0	18,0	8,8	1,1	18	500	2.000
03011082	16,0-18,3	19,5	10,0	7,0	24,5	19,0	8,8	1,1	18	250	2.000
03011093	17,0-19,3	20,5	10,0	7,5	25,0	20,0	9,8	1,1	18	250	1.000