



The fact that these clamps are used on very small-bore hoses means that the material of the tube or hose can sometimes be very flexible, making it more difficult to ensure a leaktight assembly due to the possible deformation of the hose. In these cases, the inner-ring is key in helping to guarantee leaktightness as well as protecting the hose from being pinched during assembly.

**MATERIAL:** Stainless steel W4  
AISI 304 1.4301  
(EN 10088-2:2005)  
Stainless steel inner-ring  
AISI 301

**CORROSION RESISTANCE:** 250 hours Salt Spray  
(ASTM B-117)

Part Number	Ø Application mm	A ±0.2	B ±0.2	C ±0.2	D +0.3-0.2	F ±0.2	G ±0.2	E +0.1-0.02	Max. Pressure (Bar)	Box Quantity U.	Outer Box Quantity U.
23012300	7,5-8,5	9,3	5,5	6,0	12,8	8,8	7,8	0,6	27	2.000	8.000
23012319	8,2-9,5	10,3	6,0	6,0	13,8	9,8	7,8	0,8	27	1.000	8.000
23012327	9,0-10,5	11,3	6,5	6,5	14,8	10,8	7,8	0,8	27	1.000	8.000
23012335	10,0-11,5	12,3	7,0	6,5	15,8	11,8	7,8	0,8	27	500	8.000
23012343	10,5-12,5	13,3	7,5	6,5	16,8	12,8	7,8	0,9	27	500	8.000
23012351	11,5-13,5	14,3	8,0	7,0	18,5	13,8	7,8	0,9	22	500	4.000
23012360	12,5-14,5	15,3	8,0	7,0	19,5	14,8	8,8	1,0	22	500	4.000
23012378	13,0-15,3	16,3	8,5	7,0	20,3	15,8	8,8	1,0	22	500	2.000
23012386	14,0-16,3	17,5	9,0	7,0	22,0	17,0	8,8	1,0	18	250	4.000
23012394	15,0-17,3	18,5	9,5	7,0	22,8	18,0	8,8	1,0	18	250	4.000
23012407	16,0-18,3	19,5	9,5	7,5	24,0	19,0	9,8	1,0	18	250	2.000
23012415	17,0-19,3	20,5	10,0	7,5	25,0	20,0	9,8	1,0	18	250	2.000