



The use of two ear clips is an economical solution for leak-tightsimple hose assemblies on hoses transporting air, gas or other fluids.

The two ears give the clip extra grip and help to maintain constant pressure around the hose. The edges are rounded to avoid damage to the hose and the assembly of this clamp is fast, safe and easy. The clamping range is greater than the one ear clip, meaning that the two-ear clip can be used on larger bore hoses. The practical design of two ear clips means that they clamp firmly onto the assembly and are tamper proof once mounted.

**MATERIAL:** Steel W1 DC04 (EN 10139)  
**FINISH:** Zinc-plated Cr3  
**CORROSION RESISTANCE:** 72 hours Salt Spray (ASTM B-117)

Part Number	Ø Application mm	A ±0.2	B ±0.2	C ±0.2	D +0.5 -0.2	E +0.1 -0.02	Max. Pressure (Bar)	Box Quantity U.	Outer Box Quantity U.
03012101	5-7	7,3	4,3	6,0	11,0	0,6	30	2.000	16.000
03012110	7-9	9,3	4,8	6,0	13,5	0,8	30	1.000	16.000
03012128	9-11	11,3	5,3	6,5	17,0	0,8	30	1.000	4.000
03012099	10-12	12,3	5,5	6,5	18,0	0,9	30	500	8.000
03012136	11-13	13,3	5,8	6,5	19,0	0,9	25	500	8.000
03012144	13-15	15,3	6,3	7,0	21,5	1,0	25	500	4.000
03012152	14-17	17,5	6,6	7,0	24,0	1,1	20	500	4.000
03012160	15-18	18,5	7,0	7,5	25,0	1,1	20	500	2.000
03012179	17-20	20,5	7,6	7,5	27,0	1,1	20	250	2.000
03012187	18-21	21,5	7,9	8,0	28,0	1,1	15	250	2.000
03012195	20-23	23,5	8,5	8,0	31,0	1,1	15	250	2.000
03012208	22-25	25,5	9,1	8,5	33,0	1,3	15	200	1.600
03012216	23-27	27,5	9,4	8,5	35,0	1,3	10	200	1.600
03012224	25-28	28,5	10,0	9,0	36,0	1,3	10	200	800
03012232	28-31	31,5	10,6	9,0	39,0	1,3	10	100	800
03012240	31-34	34,5	11,0	9,5	42,0	1,3	5	100	800
03012259	34-37	37,5	11,5	9,5	46,0	1,5	5	100	800
03012267	37-40	40,5	12,0	10,0	49,0	1,5	5	100	400
03012275	40-43	43,5	12,5	10,0	53,0	1,5	5	75	600
03012283	43-46	46,5	13,0	10,5	56,0	1,5	5	75	300