



The use of two ear clips is an economical solution for leak-tight simple hose assemblies on hoses transporting air, gas or other fluids.

The two ears give the clip extra grip and help to maintain constant pressure around the hose. The edges are rounded to avoid damage to the hose and the assembly of this clamp is fast, safe and easy. The clamping range is greater than the one ear clip, meaning that the two-ear clip can be used on larger bore hoses. The practical design of two ear clips means that they clamp firmly onto the assembly and are tamper proof once mounted.

MATERIAL: Stainless Steel W4
AISI 304 1.4301
(EN 10088-2:2005)

CORROSION RESISTANCE: 400 hours Salt Spray
(ASTM B-117)

Part Number	Ø Application mm	A ±0.2	B ±0.2	C ±0.2	D +0.5 -0.2	E +0.1 -0.02	Max. Pressure (Bar)	Box Quantity U.	Outer Box Quantity U.
23012108	5-7	7,3	4,3	6,0	11,0	0,6	30	2.000	16.000
23012116	7-9	9,3	4,8	6,0	13,5	0,8	30	1.000	16.000
23012124	9-11	11,3	5,3	6,5	17,0	0,8	30	1.000	8.000
23012298	10-12	12,3	5,5	6,5	17,5	0,8	30	500	8.000
23012132	11-13	13,3	5,8	6,5	18,8	0,8	25	500	8.000
23012140	13-15	15,3	6,3	7,0	21,3	1,0	25	500	4.000
23012159	14-17	17,5	6,6	7,0	23,8	1,0	20	500	4.000
23012167	15-18	18,5	7,0	7,5	24,8	1,0	20	500	4.000
23012175	17-20	20,5	7,6	7,5	26,8	1,0	20	250	2.000
23012183	18-21	21,5	7,9	8,0	27,8	1,0	15	250	2.000
23012191	20-23	23,5	8,5	8,0	30,3	1,0	15	250	2.000
23012204	22-25	25,5	9,1	8,5	32,8	1,2	15	200	1.600