



Wire clips are designed especially for use in low pressure applications with small bore hoses, with or without an outer helix. This is a competitively priced clip for use where high clamping force is not required. The spring steel used to manufacture this clip ensures that it adapts to the application diameter regardless of the pressure at any given moment.

MATERIAL: Spring steel
TS 2500-1 EN 10270-1 SH W1

FINISH: Zinc-plated Cr3

CORROSION RESISTANCE: 48 hours salt spray
(ASTM B-117)

Part Number	Ø D Application mm	a Max.	b Ø	K Max.	F		G		Box Quantity	Outer Box Quantity
					Max.	Min.	Max.	Min.		
02016012	7,3-7,8	5,2	1,0	9,5	14,50	14,00	12,50	12,00	1.000	8.000
02016020	7,8-8,3	5,5	1,0	9,5	14,75	14,25	12,85	12,35	1.000	8.000
02016039	8,3-8,8	5,5	1,0	9,5	15,15	14,65	13,45	12,95	1.000	8.000
02016047	8,8-9,3	5,5	1,0	9,5	15,55	15,05	14,05	13,55	1.000	8.000
02016055	9,3-9,9	5,5	1,0	9,5	16,60	16,10	14,30	13,80	1.000	8.000
02016063	9,8-10,4	6,3	1,2	13,0	18,55	17,55	16,55	15,55	1.000	8.000
02016071	10,4-11,0	6,3	1,2	13,0	20,15	19,15	17,75	16,75	1.000	8.000
02016080	11,0-11,6	6,3	1,2	13,0	20,45	19,45	18,55	17,55	1.000	8.000
02016098	11,6-12,3	7,3	1,5	16,0	22,35	20,85	19,15	18,35	500	4.000
02016100	12,1-13,1	7,3	1,5	16,0	23,60	22,60	20,90	20,10	500	4.000
02016119	12,9-13,6	7,3	1,5	16,0	23,65	22,65	21,45	20,65	500	4.000
02016127	13,6-14,4	7,3	1,5	16,0	25,00	24,00	22,30	21,50	500	4.000
02016135	14,4-15,1	8,4	1,8	15,0	27,10	25,60	24,80	23,30	500	4.000
02016143	14,8-15,9	8,4	1,8	16,5	28,80	27,30	25,70	24,20	500	4.000
02016151	15,9-16,8	8,4	1,8	17,0	30,20	28,70	26,30	24,80	500	4.000
02016160	16,8-17,7	8,4	1,8	17,5	29,95	28,45	26,68	25,15	500	4.000
02016178	17,7-18,7	9,6	1,9	17,5	31,80	30,30	28,30	26,80	500	2.000
02016186	18,7-19,6	9,9	2,0	18,0	32,90	31,40	29,10	27,60	500	2.000
02016194	19,6-20,5	9,9	2,0	18,0	34,00	32,60	30,10	28,60	500	2.000