



The self-locking mechanism of the cable tie incorporates a stainless-steel ball-bearing making it extremely secure once fastened. Due to its design, the stainless-steel cable tie is tamper-proof once it has been mounted.

Two different bandwidths are available, meaning that you can clamp up to 114kg, and in applications up to 300mm in diameter.

Assembly is carried out using a tool which tightens the tie to its limit and then cuts off the remaining material at the base of the housing, leaving no extra material protruding.

MATERIAL: Stainless Steel
W4 AISI 304
CORROSION RESISTANCE: 400 hours salt spray (ASTM B-117)

Part Number	a x L Dimension	Ø Max. Application	S ±0.2	W ±0.2	L1 ±0.05	H ±0.02	Resistance (N)	Box Quantity	Outer Box Quantity
03002001	4,6 x 129	39	0,25	6,55	11,00	4,40	890	100	8.000
03002002	4,6 x 200	61	0,25	6,55	11,00	4,40	890	100	5.000
03002003	4,6 x 300	93	0,25	6,55	11,00	4,40	890	100	2.000
03002004	4,6 x 370	116	0,25	6,55	11,00	4,40	890	100	2.000
03002005	4,6 x 520	163	0,25	6,55	11,00	4,40	890	100	2.000
03002006	4,6 x 680	214	0,25	6,55	11,00	4,40	890	100	2.000
03002007	4,6 x 840	265	0,25	6,55	11,00	4,40	890	100	1.000
03002008	7,9 x 197	60	0,25	11,00	13,00	5,25	1.600	100	1.000
03002009	7,9 x 300	93	0,25	11,00	13,00	5,25	1.600	100	4.000
03002010	7,9 x 368	115	0,25	11,00	13,00	5,25	1.600	100	3.000
03002011	7,9 x 450	141	0,25	11,00	13,00	5,25	1.600	100	2.000
03002012	7,9 x 500	157	0,25	11,00	13,00	5,25	1.600	100	2.000
03002013	7,9 x 680	214	0,25	11,00	13,00	5,25	1.600	100	1.000
03002014	7,9 x 1.020	323	0,25	11,00	13,00	5,25	1.600	100	500