



This nylon cable tie made of 6.6 polyamide is quick to apply thanks to its easy-to-place head design, as the bent tip facilitates introducing the part. It has smooth edges that prevent damage to the surface where it is applied and position-locking inner teeth that prevent slip and make the cable tie highly resistant to breaking. Compliant with RoHS standards.

MATERIAL: Polyamide 6.6
Halogen-free

REGULATION: EN 62275/15 - RoHS
Directive (2015/863/EU)
Tensile test according to UL 62275

Size W x L	Part Number	W	L	Ø Maximum Application	Resistance kg	Box Quantity	Outer Box Quantity
2,5 x 100	0300003Y	2,5	100	22	8,1	100	50.000
2,5 x 160	0300006Y	2,5	160	40	8,1	100	35.000
3,6 x 140	0300011Y	3,6	140	33	18,2	100	28.000
3,6 x 200	0300014Y	3,6	200	53	18,2	100	18.000
3,6 x 370	0300017Y	3,6	370	102	18,2	100	11.000
4,8 x 160	0300019Y	4,8	160	38	22,2	100	16.000
4,8 x 200	0300021Y	4,8	200	50	22,2	100	15.000
4,8 x 250	0300023Y	4,8	250	60	22,2	100	12.000
4,8 x 300	0300026Y	4,8	300	76	22,2	100	11.000
4,8 x 370	0300027Y	4,8	370	102	22,2	100	10.000
4,8 x 390	0300028Y	4,8	390	105	22,2	100	8.000

Up to size 4.8 x 390 also available in bags of 10 packs (1,000 pieces).