

# ASFA High Torque (16 mm) Hose Clamp Stainless Steel W4



W4

Mikalor High-Torque Clamps were designed to guarantee maximum performance in the most demanding applications. Thanks to the use of an M8 screw and the choice of 16mm bandwidth, torque values can be applied which are far higher than those used with the standard ASFA range, thereby ensuring perfect performance in high-pressure applications. The High-Torque clamp is particularly popular in industrial and automotive applications due to its outstanding performance. The perfectly rounded bevelled band edges avoid the clamp cutting into or damaging the hose.

\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

\* Fully complies with the SAE J1508 Type HD standard and EU Directive 2002/95/EC.

Ø D Application mm	Part Number	a ±0.2	L Max.	S ±0.1	H Max.	B Max.	T	Maximum Values		Box Quantity	Outer Box Quantity
								Pressure (Bar)	Torque (Nm)		
25-45	03067001	16	40	0,8	14	22	8	55	14	50	200
32-54	03067002	16	40	0,8	14	22	8	50	14	50	200
45-67	03067003	16	40	0,8	14	22	8	45	14	50	50
57-79	03067004	16	40	0,8	14	22	8	40	14	50	50
70-92	03067005	16	40	0,8	14	22	8	30	14	50	50
83-105	03067006	16	40	0,8	14	22	8	20	14	25	25
95-118	03067007	16	40	0,8	14	22	8	17	14	25	25
108-130	03067008	16	40	0,8	14	22	8	14	14	25	25
121-143	03067009	16	40	0,8	14	22	8	11	14	25	25
133-156	03067010	16	40	0,8	14	22	8	8	14	25	25
146-168	03067011	16	40	0,8	14	22	8	6	14	25	25
159-181	03067012	16	40	0,8	14	22	8	5	14	25	25
172-194	03067013	16	40	0,8	14	22	8	4	14	25	25
184-206	03067014	16	40	0,8	14	22	8	3	14	25	25
197-219	03067015	16	40	0,8	14	22	8	2	14	25	25
210-232	03067016	16	40	0,8	14	22	8	2	14	25	25
223-245	03067017	16	40	0,8	14	22	8	2	14	25	25
236-258	03067018	16	40	0,8	14	22	8	2	14	25	25
249-271	03067019	16	40	0,8	14	22	8	2	14	25	25
262-284	03067020	16	40	0,8	14	22	8	2	14	25	25
275-297	03067021	16	40	0,8	14	22	8	2	14	25	25
288-310	03067022	16	40	0,8	14	22	8	2	14	25	25

TECHNICAL INFORMATION	
<b>MATERIAL</b>	Stainless steel band and housing W4 AISI 304 X5Cr Ni 18/10 (DIN 1.4301) Stainless steel screw W4 AISI 304 Cu
<b>CORROSION RESISTANCE</b>	400 hours salt spray (ASTM B-117)
<b>MAX. TIGHTENING SPEED (RPM)</b>	540 ± 5

