



W2

## ASFA-S (12 mm) Hose Clamp Stainless Steel W2 DIN 3017

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

**\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
16-27	03017017	12	29,6	0,85	11	16,7	45,0	5,0	50	400
20-32	03017025	12	29,6	0,85	11	16,7	45,0	6,0	50	400
25-40	03017033	12	29,6	0,85	11	16,7	40,0	6,0	50	400
30-45	03017009	12	29,6	0,85	11	16,7	35,0	6,0	50	400
32-50	03017041	12	29,6	0,85	11	16,7	35,0	6,5	50	200
40-60	03017050	12	29,6	0,85	11	16,7	30,0	6,5	50	400
50-70	03017068	12	29,6	0,85	11	16,7	25,0	7,5	50	400
60-80	03017076	12	29,6	0,85	11	16,7	20,0	7,5	50	50
70-90	03017084	12	29,6	0,85	11	16,7	17,0	7,5	50	50
80-100	03017092	12	29,6	0,85	11	16,7	14,0	7,5	25	200
90-110	03017105	12	29,6	0,85	11	16,7	12,0	7,5	25	200
100-120	03017113	12	29,6	0,85	11	16,7	10,0	7,5	25	200
110-130	03017121	12	29,6	0,85	11	16,7	8,0	7,5	25	25
120-140	03017130	12	29,6	0,85	11	16,7	7,0	7,5	25	25
130-150	03017148	12	31,6	0,85	11	16,7	6,0	7,5	25	25
140-160	03017156	12	31,6	0,85	11	16,7	5,0	7,5	25	25
150-170	03017164	12	31,6	0,85	11	16,7	4,0	7,5	25	25
160-180	03017172	12	31,6	0,85	11	16,7	3,0	7,5	25	25
170-190	03017180	12	31,6	0,85	11	16,7	2,0	7,5	10	10



## ASFA-S (12 mm) Hose Clamp Stainless Steel W2 DIN 3017



W2


This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

**\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
180-200	03017199	12	31,6	0,85	11	16,7	2,0	7,5	10	10
190-210	03017201	12	31,6	0,85	11	16,7	1,8	7,5	10	10
200-220	03017210	12	31,6	0,85	11	16,7	1,8	7,5	10	10
210-230	03017228	12	31,6	0,85	11	16,7	1,6	7,5	10	10
220-240	03017236	12	31,6	0,85	11	16,7	1,6	7,5	10	10
230-250	03017245	12	31,6	0,85	11	16,7	1,6	7,5	10	10
240-260	03017253	12	31,6	0,85	11	16,7	1,6	7,5	10	10
250-270	03017261	12	31,6	0,85	11	16,7	1,6	7,5	10	10
260-280	03017278	12	31,6	0,85	11	16,7	1,6	7,5	10	10
270-290	03017288	12	31,6	0,85	11	16,7	1,6	7,5	10	10
280-300	03017296	12	31,6	0,85	11	16,7	1,6	7,5	10	10
290-310	03017309	12	31,6	0,85	11	16,7	1,6	7,5	10	10

TECHNICAL INFORMATION	
	<p><b>MATERIAL</b></p> <p>Stainless steel band and housing W2 AISI 430 X6Cr17 (DIN 1.4016) Steel screw Qst 36-3 (DIN 1.0214) Zinc plated Cr3</p>
	<p><b>CORROSION RESISTANCE</b></p> <p>72 hours salt spray (ASTM B-117)</p>
	<p><b>MAX. TIGHTENING SPEED (RPM)</b></p> <p>540 ± 5</p>

