



W3

## ASFA-S (12 mm) Hose Clamp Stainless Steel W3 DIN 3017

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

**\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
16-27	03016209	12	29,6	0,8	11	16,7	45,0	4,5	50	400
20-32	03016217	12	29,6	0,8	11	16,7	45,0	5,5	50	400
25-40	03016225	12	29,6	0,8	11	16,7	40,0	5,5	50	400
30-45	03016233	12	29,6	0,8	11	16,7	35,0	5,5	50	400
32-50	03016241	12	29,6	0,8	11	16,7	35,0	6,0	50	200
40-60	03016250	12	29,6	0,8	11	16,7	30,0	6,0	50	400
50-70	03016268	12	29,6	0,8	11	16,7	25,0	7,0	50	400
60-80	03016276	12	29,6	0,8	11	16,7	20,0	7,0	50	50
70-90	03016284	12	29,6	0,8	11	16,7	17,0	7,0	50	50
80-100	03016292	12	29,6	0,8	11	16,7	14,0	7,0	25	200
90-110	03016305	12	29,6	0,8	11	16,7	12,0	7,0	25	200
100-120	03016313	12	29,6	0,8	11	16,7	10,0	7,0	25	200
110-130	03016321	12	29,6	0,8	11	16,7	8,0	7,0	25	25
120-140	03016330	12	29,6	0,8	11	16,7	7,0	7,0	25	25
130-150	03016348	12	31,6	0,8	11	16,7	6,0	7,0	25	25
140-160	03016356	12	31,6	0,8	11	16,7	6,0	7,0	25	25
150-170	03016364	12	31,6	0,8	11	16,7	6,0	7,0	25	25
160-180	03016372	12	31,6	0,8	11	16,7	3,0	7,0	25	25
170-190	03016380	12	31,6	0,8	11	16,7	2,0	7,0	10	10



## ASFA-S (12 mm) Hose Clamp Stainless Steel W3 DIN 3017



W3


This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

**\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
180-200	03016399	12	31,6	0,8	11	16,7	1,8	7,0	10	10
190-210	03016428	12	31,6	0,8	11	16,7	1,8	7,0	10	10
200-220	03016436	12	31,6	0,8	11	16,7	1,8	7,0	10	10
210-230	03016444	12	31,6	0,8	11	16,7	1,6	7,0	10	10
220-240	03016452	12	31,6	0,8	11	16,7	1,6	7,0	10	10
230-250	03016712	12	31,6	0,8	11	16,7	1,6	7,0	10	10
240-260	03016723	12	31,6	0,8	11	16,7	1,6	7,0	10	10
250-270	03016734	12	31,6	0,8	11	16,7	1,6	7,0	10	10
260-280	03016745	12	31,6	0,8	11	16,7	1,6	7,0	10	10
270-290	03016756	12	31,6	0,8	11	16,7	1,6	7,0	10	10
280-300	03016767	12	31,6	0,8	11	16,7	1,6	7,0	10	10
290-310	03016768	12	31,6	0,8	11	16,7	1,6	7,0	10	10

TECHNICAL INFORMATION	
	<p><b>MATERIAL</b></p> <p>Stainless steel band and housing W3 AISI 430 X6Cr17 (DIN 1.4016) Stainless steel screw W4 AISI 304 Cu</p>
	<p><b>CORROSION RESISTANCE</b></p> <p>200 hours salt spray (ASTM B-117)</p>
	<p><b>MAX. TIGHTENING SPEED (RPM)</b></p> <p>540 ± 5</p>

