



W4

ASFA-S (12 mm) Hose Clamp Stainless Steel W4 DIN 3017

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

*** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
16-27	03014730	12	29,6	0,8	11	16,7	45,0	5,0	50	400
20-32	03014510	12	29,6	0,8	11	16,7	45,0	6,0	50	400
25-40	03014529	12	29,6	0,8	11	16,7	40,0	6,0	50	400
30-45	03014748	12	29,6	0,8	11	16,7	35,0	6,0	50	400
32-50	03014537	12	29,6	0,8	11	16,7	35,0	6,5	50	200
40-60	03014545	12	29,6	0,8	11	16,7	30,0	6,5	50	400
50-70	03014553	12	29,6	0,8	11	16,7	25,0	7,5	50	400
60-80	03014561	12	29,6	0,8	11	16,7	20,0	7,5	50	50
70-90	03014570	12	29,6	0,8	11	16,7	17,0	7,5	50	50
80-100	03014588	12	29,6	0,8	11	16,7	14,0	7,5	25	200
90-110	03014596	12	29,6	0,8	11	16,7	12,0	7,5	25	200
100-120	03014609	12	29,6	0,8	11	16,7	10,0	7,5	25	200
110-130	03014617	12	29,6	0,8	11	16,7	8,0	7,5	25	25
120-140	03014625	12	29,6	0,8	11	16,7	7,0	7,5	25	25
130-150	03014633	12	31,6	0,8	11	16,7	6,0	7,5	25	25
140-160	03014641	12	31,6	0,8	11	16,7	5,0	7,5	25	25
150-170	03014650	12	31,6	0,8	11	16,7	4,0	7,5	25	25
160-180	03014668	12	31,6	0,8	11	16,7	3,0	7,5	25	25
170-190	03014676	12	31,6	0,8	11	16,7	2,0	7,5	10	10



ASFA-S (12 mm) Hose Clamp Stainless Steel W4 DIN 3017



W4


This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened. Thanks to the combination of the housing, the locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

The ASFA S hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

*** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
180-200	03014684	12	31,6	0,8	11	16,7	2,0	7,5	10	10
190-210	03014692	12	31,6	0,8	11	16,7	1,8	7,5	10	10
200-220	03014705	12	31,6	0,8	11	16,7	1,8	7,5	10	10
210-230	03014713	12	31,6	0,8	11	16,7	1,6	7,5	10	10
220-240	03014721	12	31,6	0,8	11	16,7	1,6	7,5	10	10
230-250	03014783	12	31,6	0,8	11	16,7	1,6	7,5	10	10
240-260	03014751	12	31,6	0,8	11	16,7	1,6	7,5	10	10
250-270	03014772	12	31,6	0,8	11	16,7	1,6	7,5	10	10
260-280	03014794	12	31,6	0,8	11	16,7	1,6	7,5	10	10
270-290	03014923	12	31,6	0,8	11	16,7	1,6	7,5	10	10
280-300	03014935	12	31,6	0,8	11	16,7	1,6	7,5	10	10
290-310	03014947	12	31,6	0,8	11	16,7	1,6	7,5	10	10

TECHNICAL INFORMATION	
	<p>MATERIAL</p> <p>Stainless steel band and housing W4 AISI 304 X5Cr Ni 18/10 (DIN 1.4301) Stainless steel screw W4 AISI 304 (DIN 1.4567)</p>
	<p>CORROSION RESISTANCE</p> <p>400 hours salt spray (ASTM B-117)</p>
	<p>MAX. TIGHTENING SPEED (RPM)</p> <p>540 ± 5</p>

