

OEM Ear Clip W1



W1


This clamp was designed for use in low and medium-pressure applications on assembly lines, due to its fast and easy locking system.

The design of the locking mechanism means that this clamp can be used in areas which are difficult to access. In this case, manual pliers can be used to mount the clip.

Another very important characteristic of this clamp is that, once it has been mounted, it is tamper-proof.

**This clamp is also available in AISI 304 and AISI 316 material upon request.*

Ø A ±0.3 mm	Part Number	Ø B Closed	C ±0.5	D ±0.5	E ±0.1	F +0.4 -0.1	G Max.	Box Quantity	Outer Box Quantity
10,0	03030752	8,3	8	2,6	0,6	7	14,0	1.000	4.000
13,3	03030760	10,8	8	2,6	0,6	7	17,5	1.000	4.000
15,7	03030779	13,2	8	2,8	0,6	7	19,9	1.000	4.000
17,5	03030787	14,3	8	2,8	0,8	7	22,5	1.000	4.000
17,8	03030795	14,6	8	2,8	0,8	7	22,5	1.000	4.000
18,5	03030808	15,3	8	2,8	0,8	7	23,5	1.000	4.000
20,5	03030816	17,3	8	2,8	0,8	7	26,0	500	2.000
29,5	03030824	26,3	8	2,8	0,8	7	35,5	500	2.000
31,6	03030832	28,4	8	2,8	0,8	7	37,5	500	2.000
39,6	03030840	36,4	8	2,8	0,8	7	45,5	500	500
40,5	03030859	37,3	8	2,8	0,8	7	46,5	500	500
45,5	03030867	42,3	8	2,8	0,8	7	51,5	200	800
47,0	03030875	43,8	8	2,8	0,8	7	53,0	200	1.600
51,5	03030883	48,3	8	2,8	0,8	7	57,5	100	800
52,5	03030891	49,3	8	2,8	0,8	7	58,5	100	800
65,5	03030904	62,3	8	2,8	0,8	7	71,5	100	800

TECHNICAL INFORMATION	
	<p>MATERIAL</p> <p>Steel W1 DX51D+AZ 150 (EN 10215)</p> <p>CORROSION RESISTANCE</p> <p>144 hours salt spray (ASTM B-117)</p>

