



The use of malleable mild steel in the manufacture of the "Normal" mini clip means that when tightened, the clip adapts perfectly to the hose, clamping firmly but gently.

This clip is recommended for use with gaseous fluids at low pressure and on small-bore or thin-walled hoses.

"Normal" also has many applications in the automotive industry.

*The maximum pressure may vary depending on the type of hose and coupling used.

MATERIAL: Steel W1 St 02Z (DIN 1.0226)
Grade 5.8 steel screw
Grade 5 steel nut

FINISH: Zinc-plated Cr3

CORROSION RESISTANCE: 144 hours salt spray (ASTM B-117)

Part Number	Ø D Application mm	r	e	a	b ±1	s	Maximum values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Torque (Nm)		
03010510	6	M3	5	8,4	5,0	0,5	15,0	0,4	100	1.600
03010528	8	M3	5	9,0	6,5	0,5	14,0	0,4	100	1.600
03010536	9	M4	6	10,0	7,0	0,5	15,0	1,0	100	1.600
03010544	9,5-10	M4	6	10,0	7,0	0,5	14,0	1,0	100	1.600
03010552	10-11	M4	6	10,0	7,0	0,5	13,0	1,0	100	1.600
03010560	12-13	M4	6	10,0	7,0	0,5	12,5	1,0	100	1.600
03010579	13-14	M4	6	10,0	7,0	0,5	12,5	1,0	100	1.600
03010587	14-15	M4	6	10,0	7,0	0,5	12,0	1,0	100	1.600
03010595	15-17	M4	6	10,0	7,0	0,5	12,0	1,0	100	1.600
03010608	16-18	M4	6	10,0	7,0	0,5	11,5	1,0	100	1.600
03010616	18-20	M4	6	10,0	7,0	0,5	10,5	1,0	100	1.600
03010624	19-21	M4	6	10,0	7,0	0,5	10,5	1,0	100	800
03010632	20-22	M4	6	10,0	7,0	0,5	10,5	1,0	100	800
03010640	22-25	M4	6	10,0	7,0	0,5	9,5	1,0	100	800
03010659	23-26	M4	6	10,0	7,0	0,5	9,0	1,0	100	800
03010667	25-28	M4	6	10,0	7,0	0,5	8,5	1,0	100	800
03010675	26-29	M4	6	10,0	7,0	0,5	8,5	1,0	100	800
03010683	29-32	M4	6	10,0	7,0	0,5	8,0	1,0	100	800