

SUPRA W5 Hose Clamp Stainless Steel



W5

Due to its revolutionary swivelling bridge, Supra W5 can be mounted in the most awkward applications without having to remove the hose. It can be opened and fastened again when in place without dislodging any other parts of the clamp, making assembly much easier.


The high-strength bolt designed and manufactured by Mikalor specifically for this clamp, together with the captive nut and spacer system allow you to clamp the most demanding of hose assemblies.

* Fully complies with **RoHs EU Directive 2002/95/EC** dated 1st July 2006 and all its amendments.

*** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling**

Ø D Application mm	Part Number	Screw Metric	Ø D +1 -0.5	A ±0.3	S ±0.3	B ±0.5	E ±0.2	Maximum values		Box Quantity	Outer Box Quantity
								Pressure (Bar)	Torque (Nm)		
17-18	03013612	M6	18	18	0,6	19,8	8	40	10	50	400
18-19	03013613	M6	19	18	0,6	19,8	8	40	10	50	400
19-21	03013622	M6	21	18	0,6	19,8	8	40	10	50	400
21-23	03013630	M6	23	18	0,6	19,8	8	40	10	50	400
23-25	03013649	M6	25	18	0,6	19,8	8	40	10	50	400
25-27	03013657	M6	27	18	0,6	19,8	8	40	10	50	400
27-29	03013665	M6	29	18	0,6	19,8	8	40	10	50	200
29-31	03013673	M7	31	20	0,8	22,0	10	35	13	50	50
31-34	03013681	M7	34	20	0,8	22,0	10	35	13	50	50
34-37	03013690	M7	37	20	0,8	22,0	10	35	13	50	50
37-40	03013702	M7	40	20	0,8	22,0	10	35	13	50	50
40-43	03013710	M7	43	20	0,8	22,0	10	35	13	50	50
43-47	03013729	M7	47	20	0,8	22,0	10	35	16	50	50
47-51	03013737	M7	51	20	0,8	22,0	10	30	16	50	50
51-55	03013745	M7	55	20	0,8	22,0	10	30	16	25	25
55-59	03013753	M7	59	20	0,8	22,0	10	30	16	25	25
59-63	03013761	M7	63	20	0,8	22,0	10	30	16	25	25
63-68	03013770	M7	68	20	0,8	22,0	10	30	16	25	25
68-73	03013788	M8	73	25	1,0	27,5	13	20	30	25	25
73-79	03013796	M8	79	25	1,0	27,5	13	20	30	25	25
79-85	03013809	M8	85	25	1,0	27,5	13	20	30	25	25
85-91	03013817	M8	91	25	1,0	27,5	13	15	30	25	25
91-97	03013825	M8	97	25	1,0	27,5	13	15	30	25	25
97-104	03013833	M8	104	25	1,0	27,5	13	15	30	25	25
104-112	03013841	M8	112	25	1,0	27,5	13	10	30	25	25
112-121	03013850	M8	121	25	1,0	27,5	13	10	30	25	25
121-130	03013868	M8	130	25	1,0	27,5	13	10	30	25	25
130-140	03013876	M10	140	28	1,2	31,0	17	6	45	10	10
140-150	03013884	M10	150	28	1,2	31,0	17	6	45	10	10

Ø D Application mm	Part Number	Screw Metric	Ø D +1 -0.5	A ±0.3	S ±0.3	B ±0.5	E ±0.2	Maximum values		Box Quantity	Outer Box Quantity
								Pressure (Bar)	Torque (Nm)		
150-162	03013892	M10	162	28	1,2	31,0	17	6	45	10	10
162-174	03013905	M10	174	28	1,2	31,0	17	3	45	10	10
174-187	03013913	M10	187	28	1,2	31,0	17	3	45	10	10
187-200	03013921	M10	200	28	1,2	31,0	17	3	45	10	10
200-213	03013930	M10	213	28	1,2	31,0	17	3	45	10	10
213-226	03013948	M10	226	28	1,2	31,0	17	3	45	10	10
226-239	03013956	M10	239	28	1,2	31,0	17	3	45	10	10
239-252	03013964	M10	252	28	1,2	31,0	17	3	45	10	10
252-265	03013971	M10	265	28	1,2	31,0	17	3	45	10	10
265-278	03013981	M10	278	28	1,2	31,0	17	3	45	10	10
278-291	03013982	M10	291	28	1,2	31,0	17	3	45	10	10
291-304	03013983	M10	304	28	1,2	31,0	17	3	45	10	10
304-317	03013984	M10	317	28	1,2	31,0	17	3	45	10	10
317-330	03013985	M10	330	28	1,2	31,0	17	3	45	10	10
330-343	03013986	M10	343	28	1,2	31,0	17	3	45	10	10
343-356	03013991	M10	356	28	1,2	31,0	17	3	45	10	10
356-369	03013992	M10	369	28	1,2	31,0	17	3	45	10	10
369-382	03013993	M10	382	28	1,2	31,0	17	3	45	10	10
382-395	03013994	M10	395	28	1,2	31,0	17	3	45	10	10
395-408	03013995	M10	408	28	1,2	31,0	17	3	45	10	10

TECHNICAL INFORMATION	
	MATERIAL Stainless steel band W5 AISI 316 X5CrNi Mo1712 (DIN 1.4404) Stainless steel screw W5 AISI 316
	CORROSION RESISTANCE 1.000 hours salt spray (ASTM B-117)
	MAX. TIGHTENING SPEED (RPM) 540 ± 5

